



OSW Equipment & Repair, LLC

OSW STEEL TRUCK BODY TUB STYLE MODEL - SDBTUB SIMPLE 18

		Initial	
Floor:	4 MM AR450 Steel		
Floor Length:	23'-6"		
Truck Cab to Axle:	SALES TO ENTER		
Truck Wheelbase:	SALES TO ENTER		
Cab to Body Gap:	SALES TO ENTER		
Rear Overhang:	SALES TO ENTER		
Sides:	3 MM AR450 Steel		
Width:	Inside Width of the Box 87"		
Side Height:	54" Tall front to rear		
	V groove (Corrugation) formed in for strength		
	just above center, with dash cut out for v groove		
Top Rails:	3 MM AR450 Steel Formed In. Top on Diamond		
Tarp System:	"LC" Electric Arm Tarp with mesh tarp and alum housing		
	Tarp Motor on passenger side, pointing down		
Tarp Location:	Top Mount - High Mount		
Front Panel:	3 MM AR450 Steel, to be 60" Tall.		
	Cut dash to form with V groove on side		
Load Sight Window:	With a Steel mesh loading window, 6 1/2" tall X 12" wide.		
Shovel Holder:	YES on driver side		
Cab Guard:	NONE		
Tailgate:	3/16" ALUM Tailgate		
	Straight 90 Degrees & height to match sides		
	(4) -3/16" Formed Channels Located Vertically.		
	Hazard Waste Locks.		
	Brace Inside of Tailgate on Top, Side, and Bottom		
Tailgate Locks:	2.5" x 6" Air Operated Cylinder - Electric over Air Operation		
Longitudinals:	3/16" Hi-Tensile Steel, 8" Tall		
Corner Posts:	3/16" Hi-Tensile Steel		
Fenders:	3/16" Smooth alum bolt on,		
	with bottom flange wide enough to hold 2" Marker lites		
Front Fender Extensions:	YES - Steel With Grip Tape		



OSW Equipment & Repair, LLC

OSW STEEL TRUCK BODY TUB STYLE MODEL - SDBTUB SIMPLE 18

SPREADER APRON:	NONE		
Spreader Chains:	(2) 3/8" HD Chains Welded to Underside of Rear Cross Member. Chains Hooked to Slotted Brackets on Tailgate.		
Side Board	Alum side boards		
Steps & Handles:	(3) - Steps driver side at front corner evenly spaced, To be wrap around driver side front corner (2) - steps inside body on front wall driver side. (1) - Grab handle on front side board pocket driver side.		
Cylinder:	Power Up / Gravity Down		
Mount Style:	External Trunnion		
PTO:	Hot Shift PTO		
Transmission Make:	SALES TO ENTER		
Model:	SALES TO ENTER		
Pump:	Single Valve on Pump		
Valve:	Single Valve/Pump Combo		
Controls:	Single Lever Broom-stick right side of driver seat Electric/Air switch on dash for Tailgate.		
Oil Tank:	50 Gallon Rectangular Formed Alum Tank Includes 2" Suction Port, 1.5" Return Port, 2" Filler Port, 1 Top Mounted Breather Port & Side Mounted Sight Tube Mounted on Saddle with Hoist.		
BODY UP SENSOR:	Yes		
Rear Hinges:	Fabricated & Gusseted Tube to Hinge Pad w/Grease Zerks, 1" Ears, And 2" Hardened Pins		
Hitch:	NONE - No Pony Package		
CHIP BAR:	NONE		



OSW Equipment & Repair, LLC

OSW STEEL TRUCK BODY TUB STYLE MODEL - SDBTUB SIMPLE 18

Lights:	ICC/DOT Legal Lights. Grommet Mounted LED's.		
	(1) - Marker Per Side at front in top rail		
	(2) - Markers per Corner Post; One Rearward Facing; One Side Mounted.		
	(1) - Oval Stop/Turn/Tail per corner post		
	(1) - Oval Back up light wired to reverse.		
	Back up light to be mounted above taillight		
	(5) -extra marker lights in EACH fender [10 Total]. Four 2" Markers		
	With One Oval Marker/Turn Signal Set Forward of Center Fender Split.		
	View Train Drawing for Locations		
Rear Crossmember:	(4 Lights Total) - Two Stop Turn Tail (outer) and Two Back Up (inner)		

Mud Flaps: OSW 30" HD Rubber Flaps
REAR FLAPS TO BE AIR LIFT

Paint: **Dark Green F9891EY (Crossed to 410094)** Includes D.O.T. Conspicuity Taping.

Truck Dimensions: **Need Before Body Can Be Release From Engineering**

LIFT AXLE: **WATSON & Chalin 8000lb lift axle assy installed with polished alum**
17.5X6 alum wheel and Goodyear G114 215/75R17.5

