



# OSW Equipment & Repair, LLC

## TRUCK BODY - STEEL STD - TAPERED SDBTS

T References:		Initial	
Quote Number:	SALES TO ENTER		
Truck Make:	SALES TO ENTER		
Truck Model:	SALES TO ENTER		
Truck Cab to Axle:	SALES TO ENTER		
Truck Wheelbase:	SALES TO ENTER		
Cab to Body Gap:	SALES TO ENTER		
Rear Overhang:	SALES TO ENTER		
Hardox Option:	NO		
Body Width:	87" (SQ STD)		
Body Length:	16'6" (SQ STD)		
Floor:	3/16" AR450 Steel (SQ STD)		
Sides:	10GA GR50 Steel (SQ STD)		
Side Height:	47-1/2" at the Front That Tapers to 35" at the Rear (SDBTS STD)		
Longitudinals:	3/16" GR50 Steel 8" (SQ STD)		
Top Rails:	10GA GR50 Steel (SQ STD)		
Top Rail Style:	Standard - Flat Top		
Mid Rails:	10GA GR50 Steel (SQ STD)		
Bulkhead:	3/16" GR50 Steel (SQ STD)		
Corrugated:	YES (STD)		
Shovel Holder:	YES - Driver Side		
Corner Posts:	3/16" GR50 Steel (SQ STD)		
Tail Light Style:	Round (STD)		
Mount Style:	Doghouse		
Material:	3/16" AR450 Steel (Dog House STD)		
Hi Lift:	NO		
Trailer Body Hi Lift:	NO		
Tailgate :	10 GA GR50 Steel (SQ STD)		
	(4 Total) - 10 GA. Formed Channels Located Horizontally (1) Top, (2) Middle, (1) Bottom - Hinged at Top with 1.25" Pins		
Tailgate Angle:	20 Degrees (STD)		



# OSW Equipment & Repair, LLC

## TRUCK BODY - STEEL STD - TAPERED SDBTS

T References:		Initial	
<b>Asphalt Gates:</b> *	0		
<b>Asphalt Gate Width:</b>	N/A		
<b>Air Operated:</b>	NO		
<b>Cab Guard:</b>	10GA A36 Steel (STD)		
<b>Height:</b>	72" (SQ STD)		
<b>Tailgate Locks:</b>	Electric Over Air Operation - 2.5" x 6" Air Operated Cylinder (STD)		
<b>Hazard Locks:</b> *	2 (STD) Cannot Have Tailgate Opener		
<b>Waste Seal:</b>	NO		
<b>Chain Retainers:</b>	4 (STD)		
<b>Tailgate Opener:</b>	NO		
<b>Tarp System:</b>	NO		
<b>Mount Location:</b>	NO		
<b>Tarp Material:</b>	N/A		
<b>Tarp Color:</b>	N/A		
<b>Integrated Housing:</b>	NO		
<b>Motor Location:</b>	N/A		
<b>Trailer Tarp Wiring:</b>	YES		
<b>Side Boards:</b>	Brackets/Pockets ONLY (Standard)		
<b>Top Board Angle:</b>	NO		
<b>Plywood Lining:</b>	NO		
<b>Steps &amp; Handles:</b>	(1) Mounted on Midrail, (1) Bottom of Sidewall, (1) Front Driverside Inner Corner (STD)		
<b>Add Steps:</b>	NO		
<b>Add Handle:</b>	NO		
<b>Full Walk Rail:</b>	NO		
<b>Fold Down Ladder:</b>	NO		
<b>Fenders:</b>	10GA GR50 Steel (SQ STD)		
<b>Fender Overlays:</b>	NO		
<b>Spray Guards:</b>	NO		



# OSW Equipment & Repair, LLC

## TRUCK BODY - STEEL STD - TAPERED SDBTS

T References:	Initial		
<b>Body Lights:</b>	<i>ICC/DOT Legal Lights Grommet Mounted LED's</i>		
<b>Markers:</b>	(2) 2" Marker Per Corner Post		
<b>Stop, Turn, Tail:</b>	2 Per Side		
<b>Midrail Lights:</b>	1 Per Side (2 Total STD)		
<b>Midrail Light Size:</b>	2"		
<b>Additional Lights:</b>	NO		
<b>Chassis Lights:</b>	ICC Light Cluster at Rear		
<b>Rear Light Plate:</b>	(2) - Stop, Turn, Tail Lights & (1) - Backup Light		
<b>Mud Flaps:</b>	<i>OSW 30" HD Rubber Flaps Mounted Front, Mid, and Rear *See Truck Drawing for Dimensions*</i>		
<b>Backup Camera:</b>	NO		
<b>PTO:</b>	Chelsea Air Shift PTO (Standard) *PTO Will Have Factory Supplied Switch, Wiring, and Program		
<b>Transmission Make:</b>	<b>SALES TO ENTER</b>		
<b>Transmission Model:</b>	<b>SALES TO ENTER</b>		
<b>Pump:</b>	Direct Mount P51 Pump (STD)		
<b>Valve:</b>	2 Spool Valve - Parker (SQ STD)		
<b>Cylinder:</b>	Match Body Length		
<b>Control Power:</b>	Cable (STD)		
<b>Control Mount:</b>	Console (STD)		
<b>Oil Tank:</b>	10GA Hi-Tensile Formed Steel - 35 Gal Capacity		
<b>Body Vibrator:</b>	* NO		
<b>Rear Hinges:</b>	Standard <i>Heavy Duty Hinged Pad Assembly with 1" Thick Ears, 2" Hardened Pins, and Grease Fittings</i>		
<b>Body Scales:</b>	NO		



# OSW Equipment & Repair, LLC

## TRUCK BODY - STEEL STD - TAPERED SDBTS

T References:	Initial
<b>Chip Bar:</b> NO	
<b>Hitch:</b> YES	
<b>Height:</b> 24" (OSW Standard)	
<b>Location:</b> Rear Of Tire is Flush with Forward Inner Face of Pintle	
<i>Use Hitch &amp; Chip Bar Page for Dimensions</i>	
<b>Backup Alarm:</b> NO	
<b>Spreader Chains:</b> YES (STD)	
<b>Body Color:</b> OSW Silver (STD)	
<b>Tailgate Color:</b> OSW Silver (STD)	
<b>Chassis Color:</b> OSW Black (STD)	
<b>Cylinder Color:</b> OSW Black (STD)	
<i>Includes D.O.T. Conspicuity Taping</i>	
<b>Delivery Date Desired:</b>	
<b>Cab Arrival Date:</b>	

Additional Notes:	Initials

All OSW Specifications Will Be STANDARD Build, Unless Stated Above or NOTED in Received "Printed Specification Sheet." Items Involving Engineering Will Require Longer Build Time.

**Name:** \_\_\_\_\_