



# OSW Equipment & Repair, LLC.

## TRUCK BODY - STEEL STD TUB - STRAIGHT SDBSS-TUB

T References:		Initial
Quote Number:	SALES TO ENTER	
Truck Make:	SALES TO ENTER	
Truck Model:	SALES TO ENTER	
Truck Cab to Axle:	SALES TO ENTER	
Truck Wheelbase:	SALES TO ENTER	
Cab to Body Gap:	SALES TO ENTER	
Rear Overhang:	SALES TO ENTER	
Hardox Option:	NO	
Body Width:	87" (STD)	
Body Length:	16'6" (STD)	
Floor:	3/16" AR450 Steel (STD)	
Rock Lip:	NO	
Sides:	3/16" AR450 Steel (STD)	
Side Height:	Straight 42" (SDBSS STD)	
Corrugated:	YES (STD)	
Longitudinals:	3/16" GR50 Steel 8" (STD)	
Top Rails:	3/16" AR450 Steel (STD)	
Top Rail Position:	Standard - Flat Top	
Bulkhead:	3/16" AR450 Steel (STD)	
Corrugated:	YES (STD)	
Shovel Holder:	YES - Driver Side	
Corner Posts:	3/16" GR50 Steel (STD)	
Tail Light Style:	Round (STD)	
Dog House:	3/16" T1 Steel (STD)	
Mount Style:	Doghouse	
Hi Lift:	NO	
Safety Hooks:	NO	
Trailer Body Hi Lift:	NO	
Tailgate :	3/16" AR450 Steel (STD) (4 Total) - 10 GA. Formed Channels Located Horizontally (1) Top, (2) Middle, (1) Bottom - Hinged at Top with 1.25" Pins	



# OSW Equipment & Repair, LLC.

## TRUCK BODY - STEEL STD TUB - STRAIGHT SDBSS-TUB

T References:	Initial
<b>Tailgate Angle:</b> 20 Degrees (STD)	<input type="checkbox"/>
-	<input type="checkbox"/>
<b>Asphalt Gates: *</b> 0	<input type="checkbox"/>
<b>Asphalt Gate Width:</b> N/A	<input type="checkbox"/>
<b>Air Operated:</b> NO	<input type="checkbox"/>
<b>Tailgate Locks:</b> Electric Over Air Operation - 2.5" x 6" Air Operated Cylinder (STD)	<input type="checkbox"/>
<b>Hazard Locks: *</b> 2 (STD)	<input type="checkbox"/>
<b>Waste Seal:</b> NO	<input type="checkbox"/>
<b>Chain Retainers:</b> 4 (STD)	<input type="checkbox"/>
<b>Tailgate Opener:</b> NO	<input type="checkbox"/>
<b>Shed Angles:</b> NO	<input type="checkbox"/>
<b>Cab Guard:</b> 10GA A36 Steel (STD)	<input type="checkbox"/>
<b>Height:</b> 72" (STD)	<input type="checkbox"/>
<b>Tarp System:</b> Tarp Mounting Brackets	<input type="checkbox"/>
<b>Mount Location:</b> High	<input type="checkbox"/>
<b>Tarp Material:</b> N/A	<input type="checkbox"/>
<b>Tarp Color:</b> N/A	<input type="checkbox"/>
<b>Integrated Housing:</b> N/A	<input type="checkbox"/>
<b>Motor Location:</b> N/A	<input type="checkbox"/>
<b>Tamer Bows</b> NO	<input type="checkbox"/>
<b>Trailer Tarp Wiring:</b> YES	<input type="checkbox"/>
<b>Side Boards:</b> Brackets/Pockets ONLY (Standard)	<input type="checkbox"/>
<b>Top Board Angle:</b> NO	<input type="checkbox"/>
<b>Plywood Lining:</b> NO	<input type="checkbox"/>
<b>Steps &amp; Handles:</b> (1) Mounted on Outer Middle & (1) Outer Lower Step Front Driver Side, (1) Front Driverside Inner Corner (STD)	<input type="checkbox"/>
<b>Add Mid Step:</b> NO	<input type="checkbox"/>
<b>Add Handle:</b> NO	<input type="checkbox"/>
<b>Full Walk Rail:</b> NO	<input type="checkbox"/>
<b>Fold Down Ladder:</b> NO	<input type="checkbox"/>
<b>Cylinder:</b> Match Body Length	<input type="checkbox"/>
<b>Fenders:</b> 10GA Steel	<input type="checkbox"/>
<b>Spray Guards:</b> NO	<input type="checkbox"/>



# OSW Equipment & Repair, LLC.

## TRUCK BODY - STEEL STD TUB - STRAIGHT SDBSS-TUB

T References:	Initial
<b>PTO:</b> Chelsea Air Shift PTO (Standard)	[ ] [ ]
*PTO Will Have Factory Supplied Switch, Wiring, and Program	
<b>Transmission Make:</b> SALES TO ENTER	[ ] [ ]
<b>Transmission Model:</b> SALES TO ENTER	[ ] [ ]
<b>Pump:</b> Direct Mount P51 Pump (STD)	[ ] [ ]
<b>Valve:</b> 2 Spool Valve - Parker (STD)	[ ] [ ]
-	[ ] [ ]
<b>Control Power:</b> Cable (STD)	[ ] [ ]
<b>Control Mount:</b> Console (STD)	[ ] [ ]
<b>Oil Tank:</b> 10GA Hi-Tensile Formed Steel - 35 Gal Capacity	[ ] [ ]
<b>Body Vibrator:</b> * NO	[ ] [ ]
<b>Rear Hinges:</b> Standard	[ ] [ ]
<i>Heavy Duty Hinged Pad Assembly with 1" Thick Ears, 2" Hardened Pins, and Grease Fittings</i>	
<b>Body Scales:</b> NO	[ ] [ ]
<b>Chip Bar:</b> NO	[ ] [ ]
-	[ ] [ ]
<b>Hitch:</b> YES	[ ] [ ]
<b>Height:</b> 24" (OSW Standard)	[ ] [ ]
<b>Location:</b> Rear Of Tire is Flush with Forward Inner Face of Pintle	[ ] [ ]
<i>Use Hitch &amp; Chip Bar Page for Dimensions</i>	
<b>Lights:</b> ICC/DOT Legal Lights Grommet Mounted LED's	[ ] [ ]
<b>Markers:</b> (2) 2" Marker Per Corner Post	[ ] [ ]
<b>Stop, Turn, Tail:</b> 2 Per Side	[ ] [ ]
<b>Top Rail Lights:</b> 1 Per Side (2 Total STD)	[ ] [ ]
<b>Top Rail Light Size:</b> 2"	[ ] [ ]
<b>Additional Lights:</b> NO	[ ] [ ]
<b>Special Wiring Notes:</b>	[ ] [ ]



# OSW Equipment & Repair, LLC.

## TRUCK BODY - STEEL STD TUB - STRAIGHT SDBSS-TUB

T References:		Initial	
Backup Camera:	NO		
Backup Alarm:	NO		
Spreader Chains:	YES (STD)		
Mud Flaps:	<i>OSW 30" HD Rubber Flaps Mounted Front, Mid, and Rear *See Truck Drawing for Dimensions*</i>		
Body Color:	OSW Silver (STD)		
Tailgate Color:	OSW Silver (STD)		
Chassis Color:	OSW Black (STD)		
Cylinder Color	OSW Black (STD)  <i>Includes D.O.T. Conspicuity Taping</i>		
Delivery Date Desired:			
Cab Arrival Date:			

Additional Notes:	Initials

All OSW Specifications Will Be STANDARD Build, Unless Stated Above or NOTED in Received "Printed Specification Sheet." Items Involving Engineering May Require Longer Build Time.

Name: