

OSW SUPER SOLO DUMP BODY MODEL OSDEK-L 40-101-00

T Reference Numbers:		_	
Quote Number:	SALES TO ENTER		
Truck Make:	SALES TO ENTER		
Truck Model:	SALES TO ENTER		
Truck Cab to Axle	SALES TO ENTER		
Truck Wheelbase:	SALES TO ENTER		
Cab to Body Gap:	SALES TO ENTER		
Rear Overhang:	SALES TO ENTER		
_		<40	>40
	Add an "X" to a Box on Right For Maximum Length Allowed »		
-	<u> </u>		
Body Length:	18'		
Floor:	4MM AR450 Steel (STD)		
	-		
Body Width:	89" OD (STD)		
Overall Width:	102" (STD)		
Sides:	3MM AR450 Steel (STD)		
Side Height:	61" (STD)		
Z Strips:	NO		
Liner:			
Top Rails:	1/8" x 4" x 4" Tube, Set on Diamond (STD)		
Bulkhead:	4MM AR450 Steel (STD)		
-	NO		
Bottle Holder:	NO		
Chock Holder:			
Material Window:	NO		
Rear Bolster:	1/4" T1 Steel. Integrated With Trailing Axle Assembly		
Tailgate:	(2) - Light Hole Corner Posts (STD)		
Material:	3MM AR450 Steel (STD)		
Asphalt Gates:	NO		
Gate Width:	N/A		
Tailgate Locks:	Cab Controlled		
	(2) - Type 30 Spring Chambers Operate Gate Lock		
Haz Locks:	0 (STD)		
•			
Apron	NO		
Tarp System:	NO		
Tarp Material & Color:	NO		



OSW SUPER SOLO DUMP BODY MODEL OSDEK-L 40-101-00

Bracket Location:	NO		
Housing Location:	NO		
Motor Location:	NO		
Extended:	NO		
Tarp Warning Sensor:	NO		
Backup Camera:	NO		
Location:	N/A		
Load Sight Camera:	NO		
Cab Guard	NO		
Height:	N/A		
Rear Hinges:	Harvey Duty Hingard Bad Assambly with 1" Thirdy Fare 3" Hardanad Bins and Crosses Fittings		
	Heavy Duty Hinged Pad Assembly with 1" Thick, Ears, 2" Hardened Pins, and Grease Fittings		
!			
Rear Hitch Assembly:	NO		
	Air & Electric Only (If Supplied on Trk Chassis)		
•			
Fenders:	Consolly Alamaian and EOFO Evillation than the of Body Manual Englandary (VD and Consolly United Bolls (CTD)		
	Smooth Aluminum 5052 Full Length of Body. Mount Fenders w/Round Smooth Hex Head Bolts. (STD)		
Fender Extensions:	Smooth 5052 Aluminum Extensions with a Step on Driver Side		
•			
Hoist:	Mailhot 160" Power Up / Gravity Down Cylinder		
Oil Tank:	Alumainum Taul, Mauratad BOC with 40 Callana Haaahla Canaait (CTD)		
	Aluminum Tank Mounted BOC with 40 Gallons Useable Capacity (STD)		
Spreader Chains:	3/8" Heavy Duty Chains Welded to Rear Crossmember		
Chip Bar:	NO		
Side Boards:	NO		
Mud Flaps:			
	30" OSW Rubber Flaps on Rear and Front. 30" Flaps with Anti-Sail Brackets Mounted on Front Fender,		
	Panels, and Ahead of Lift Axle Tires. (STD)		
Optional Air Flaps:	NO		
Light Buckets:			
giit backetsi		<u>, </u>	
Lights:	All Lights are ICC/DOT Legal LED Lights.		
Tailgate Corner Posts:			
Markers:			



OSW SUPER SOLO DUMP BODY MODEL OSDEK-L 40-101-00

	(3) - 2" Red Marker Lights [ICC Cluster] on Maxle Axle		
•	(2) - 2" Red Markers Per Side in Rear Bolster Posts		
•	(1) - 2" Amber Marker Per Side at Front, Under Top Rail		
Rear Crossmember:	YES - (2) - Stop, Turn, Tails & (1) - Backup		
Extra Lights:	NO		
٠.		<u> </u>	
Step & Handles:	(1) - Step on Driver Side Front Fender Extension. (1) - Serrated Wrap-Around Corner Step on Driver Side Front Corner and (2) - More Evenly Spaced Between Bottom Step & Top Rail. (1) - 32" Grab Handle Mounted Vertically on Bulkhead. (2) - Formed, Serrated Steps on Inside Driver Side Front Corner of Body.		
Fold Down Ladder:	NO		
Tires & Wheels:	(2) 315/80R22.5 Tires Mounted on Alcoa Aluminum Wheels (WA State Standard)		
Transmission Make:	SALES TO ENTER		
Transmission Model:	SALES TO ENTER		
Transmission Floaci.	CALLO TO ENTER		
Installation:	Hot-Shift PTO with Direct-Mount Gear Pump. Toggle Valves for PTO, Tailgate Lock, Air Flaps(If Equipped), Maxle Lift-Axle Control and Optional Tarp Control. "PTO" and "Body UP" Lights. Aluminum Diamond Plate Valve Cover.		
Control Location:	Console Mount (STD)		
Control Type:	Cable		
Danielatai Dia data	For about a Taraballia di	г	
Regulator Bracket: Pressure Gauges:	Factory Installed		
Pressure dauges:	Factory Installed	<u> </u>	
Battery Box:	NO		
•	-		,
Body Vibrator:	NO		
Trailing Axle:	Silent Drive Maxle Arm Light Axle Assembly Connects to OSW Integrated Bolster at Rear of Body, ICC Cluster Lights Included in Panel of Maxle Booster Axle.		
Maxle Arm Length:	Short (STD)		
Maxle Safety Latch:	NO		
Maxle Disc Brakes:	NO		
Body Color:	OSW Silver (STD)		
Tailgate Color:	OSW Silver (STD)		
Chassis Color	OSW Black (STD)	 	
Cylinder Color:	OSW Silver (STD)		

Additional Body Install/Build Instructions:



OSW SUPER SOLO DUMP BODY MODEL OSDEK-L 40-101-00

All OSW Specification	s Will Be STANDARD Build, Unless Stated Above or NOTED in Received "Printed Specific Items Involving Engineering May Require Longer Build Time.	ation Si	neet."
	Customer Signature:		