



OSW Equipment & Repair, LLC.

TRUCK BODY - STEEL STD TUB - STRAIGHT SDBSS-TUB

T References:	Initial	
Quote Number:	SALES TO ENTER	
Truck Make:	SALES TO ENTER	
Truck Model:	SALES TO ENTER	
Truck Cab to Axle:	SALES TO ENTER	
Truck Wheelbase:	SALES TO ENTER	
Cab to Body Gap:	SALES TO ENTER	
Rear Overhang:	SALES TO ENTER	
Body Width:	87" (STD)	
Body Length:	16'6" (STD)	
Floor:	3/16" AR450 Steel (STD)	
Rock Lip:	NO	
Sides:	3/16" AR450 Steel (STD)	
Side Height:	Straight 42" (SDBSS STD)	
Corrugated:	YES (STD)	
Longitudinals:	3/16" GR50 Steel 8" (STD)	
Top Rails:	3/16" AR450 Steel (STD)	
Top Rail Position:	Standard - Flat Top	
Bulkhead:	3/16" AR450 Steel (STD)	
Corrugated:	YES (STD)	
Shovel Holder:	YES - Driver Side	
Corner Posts:	3/16" GR50 Steel (STD)	
Tail Light Style:	Oval (STD)	
Dog House:	3/16" T1 Steel (STD)	
Mount Style:	Doghouse	
Hi Lift:	NO	
Safety Hooks:	NO	
Trailer Body Hi Lift:	NO	
Tailgate :	3/16" AR450 Steel (STD)	
	<i>(4 Total) - 10 GA. Formed Channels Located Horizontally (1) Top, (2) Middle, (1) Bottom - Hinged at Top with 1.25" Pins</i>	



OSW Equipment & Repair, LLC.

TRUCK BODY - STEEL STD TUB - STRAIGHT SDBSS-TUB

T References:		Initial
Tailgate Angle:	20 Degrees (STD)	
	-	
Asphalt Gates: *	0	
Asphalt Gate Width:	N/A	
Air Operated:	NO	
Tailgate Locks:	Electric Over Air Operation - 2.5" x 6" Air Operated Cylinder (STD)	
Hazard Locks: *	2 (STD)	
Waste Seal:	NO	
Chain Retainers:	4 (STD)	
Tailgate Opener:	NO	
Shed Angles:	NO	
Cab Guard:	10GA A36 Steel (STD)	
Height:	72" (STD)	
Tarp System:	Tarp Mounting Brackets	
Mount Location:	High	
Tarp Material:	N/A	
Tarp Color:	N/A	
Integrated Housing:	N/A	
Motor Location:	N/A	
Tamer Bows	NO	
Trailer Tarp Wiring:	YES	
Side Boards:	Brackets/Pockets ONLY (Standard)	
Top Board Angle:	NO	
Plywood Lining:	NO	
Steps & Handles:	(1) Mounted on Outer Middle & (1) Outer Lower Step Front Driver Side, (1) Front Driverside Inner Corner (STD)	
Add Mid Step:	NO	
Add Handle:	NO	
Full Walk Rail:	NO	
Fold Down Ladder:	NO	
Cylinder:	Match Body Length	
Fenders:	10GA Steel	
Spray Guards:	NO	



OSW Equipment & Repair, LLC.

TRUCK BODY - STEEL STD TUB - STRAIGHT SDBSS-TUB

T References:	Initial		
PTO:	Air Shift PTO (Standard)		
	Mandatory Factory Supplied Switch, Wiring, and Program		
Transmission Make:	SALES TO ENTER		
Transmission Model:	SALES TO ENTER		
Pump:	Direct Mount P51 Pump (STD)		
Valve:	2 Spool Valve - Parker (STD)		
	-		
Control Power:	Cable (STD)		
Control Mount:	Console (STD)		
Oil Tank:	10GA Hi-Tensile Formed Steel - 35 Gal Capacity		
Body Vibrator:	* NO		
Rear Hinges:	Standard		
	<i>Heavy Duty Hinged Pad Assembly with 1" Thick Ears, 2" Hardened Pins, and Grease Fittings</i>		
Body Scales:	NO		
Chip Bar:	NO		
	-		
Hitch:	YES		
Height:	24" (OSW Standard)		
Location:	Rear Of Tire is Flush with Forward Inner Face of Pintle		
	<i>Use Hitch & Chip Bar Page for Dimensions</i>		
Lights:	<i>ICC/DOT Legal Lights Grommet Mounted LED's</i>		
Markers:	(2) 2" Marker Per Corner Post		
Stop, Turn, Tail:	2 Per Side		
Top Rail Lights:	1 Per Side (2 Total STD)		
Top Rail Light Size:	2"		
Additional Lights:	NO		
Special Wiring Notes:			

